



DIXON™

SECURITY CAMERAS

phone: 801.455.0413

fax: 213.536.2038

email: dixonsecurity@gmail.com

location: 1744 Segó Lily Drive
Sandy, UT 84092

ED7008TSL

HD TVI RECORDER



FEATURES:

- 8 CH HD TVI video input, 1080P recording
- Playback: 4 / 8 CH simultaneously playback; HDMI 1080P output
- Backup: USB, IE, CMS; support multi-file, file cutting when backup
- Pentaplex: live, record, playback, backup and remote operation
- DHCP, DDNS, PPPoE Network protocol, IE browse and CMS supported
- Dual stream technology; Multi-user online simultaneously
- Support PTZ preset and auto cruise, up to 128 presets and 8 cruises
- Cell phone: iPhone, Android
- Complete SDK function, easy to integrate with other applications

SPECIFICATIONS

| | |
|-------------------------|---|
| Compression Format | H.264 High Profile |
| Video Input/Output | 8xHD TVI Cameras / VGAx1: 1920x1080, HDMIx1: 1920x1080, Loop Out: No |
| Audio Input/Output | RCAX1/ RCAX1 |
| Two-way Talk | RCAX1 (share with audio input) |
| Resolution | 720p: 1280x720, 1080p: 1920x1080 |
| Frame Rate | 720p: 100fps (PAL) /120fps (NTSC); 1080p: 50fps (PAL) /60fps (NTSC) |
| Stream & Encode | 1M - 6MBps; CBR/VBR |
| Image Quality | 6 Levels |
| Alarm Input/Output | NO |
| DVD & eSATA | NO |
| Playback | 8ch Synch Playback |
| Interface | 10/100Mx1 |
| Network Stream | Support: 4ch master stream, 8ch CIF 30fps sub-stream, 4ch playback remotely |
| HDD | SATA x 1 |
| Communication Interface | RS485 x 1 |
| USB / USB Backup | USB2.0 x 2 / Support U-Disk, USB-HDD, USB-Disk Burner |
| CASE | Small 1U Case, Compact 1U Case |
| Power | DC 12v; 2A |
| Temperature, Humidity | -10°C~-50°C , 10-90% |