



DIXON™

SECURITY CAMERAS

phone: 801.455.0413

fax: 213.536.2038

email: dixonsecurity@gmail.com

location: 1744 Segó Lily Drive
Sandy, UT 84092

ED7616TDL

HD TVI RECORDER



FEATURES:

- 16 CH HD TVI video input, 1080P / 960H / 720P / D1 recording
- Intuitive and user-friendly Graphic User Interface
- Multi-mode recording: manual / timer / motion / sensor
- Playback: 8 CH simultaneously playback
- Search: time / calendar, events (sensor, motion)
- Backup via USB, network (DVD-RW (SATA) optional)
- DHCP, DDNS, PPPoE Network protocol, IE browse and CMS supported
- Remote control via IE or CMS: preview, playback, backup, PTZ and configuration
- Dual stream technology to encode recording stream and network stream respectively.
- Multi-user online simultaneously; HDMI 1080P output
- Authorization management, log review and device status review
- Supports PTZ preset and auto cruise, up to 128 presets and 8 cruises
- Supports Android, iPhone

SPECIFICATIONS

Compression Format	H.264 High Profile
Video Input/Output	16x BNC / VGAX1: 1920x1080, HDMIx1: 1920x1080, Loop Out: No
Audio Input/Output	RCAx1 / RCAx1
Two-way Talk	RCAx1 (share with audio input)
Resolution	720p: 1280x720, 1080p: 1920x1080
Frame Rate	720p: 400fps (PAL) / 480fps (NTSC); 1080p: 200fps (PAL) / 240fps (NTSC)
Stream & Encode	1M - 6Mbps; CBR/VBR
Image Quality	6 Levels; Manual, Timer and Motion
File Manage	Lock, Unlock, Reserving Time
Alarm Input/Output	16ch input, 4ch output
Triggering	Record, PTZ Move, Email, etc.
Playback / Search	8ch / Time, Motion, Single or Multi-Channel
Interface	RJ45 Giga ethernet
Protocol	TCP/IP, UDP, DHCP, DNS, PPPOE, DDNS (10 users online, dual stream)
OS / HDD	iPhone, Android / SATA x 8
Function	Multi-screen surveillance, record, snapshot, PTZ control, save the device list
RS485	RS485 x 2, connected to PTZ or keyboard
USB	USB2.0 x 2, one more mouse and another for backup
Power Supply	AC (100-240v)
Dimensions	17"x17.7"x3.5" (W*D*H)
Temperature, Humidity	0°C~-50°C, 10-90%